

D1  
Concl. 6 affixation of indicia to said single-walled panel member, said single-walled  
7 panel member having an [outer] inner surface and an [inner] outer  
8 surface, wherein said outer surface is visible when said single-walled  
9 panel member is attached to the golf bag.

---

D2 1 7. (Four times Amended) A golf bag comprising:  
2 a storage tube having an open first end and a closed second end for  
3 storing and transporting a golf club;  
4 a material attached to said storage tube forming an exterior surface  
5 for the golf bag;  
6 a carrying strap coupled to a second longitudinal side of the golf bag;  
7 and  
8 a single-walled substantially planar panel member removably  
9 coupled to a first longitudinal side of the golf bag diametrically opposite  
10 said second longitudinal side[, so that said single-walled panel member[,  
11 having an outer surface and an inner surface,] is separately detachable  
12 from said first longitudinal side of said golf bag in order to facilitate  
13 affixation of indicia to said single-walled panel member, wherein an outer  
14 surface of said single walled panel member is made of said material  
15 forming said exterior surface of the golf bag so that said outer surface is  
16 visible when said panel member is attached to the golf bag.

---

D3 1 ~~13.16.~~ (Three Times Amended) A golf bag comprising:  
2 a storage tube having an open first and a closed second end for  
3 storing a golf club after said golf club is inserted through the open first end;  
4 and

D3  
Concl.

5 a single-walled substantially planar panel member coupled to a first  
6 longitudinal side of said golf bag through a securing mechanism including  
7 a second mating securing portion around a periphery of said single-walled  
8 panel member and a first securing portion being geometrically aligned  
9 with said second mating securing portion and coupled to said first  
10 longitudinal side of said golf bag, said single-walled panel member [being]  
11 is completely detachable from said first longitudinal side of said golf bag by  
12 decoupling said second mating securing portion from said first securing  
13 portion, wherein said outer surface is visible when said single-walled  
14 panel member is attached to the golf bag.

---